

Bigger and even better

Easy-to-use controls combined with professional cleaning.

TTB6055, TTB6055T

The 55cm (20") size of TwinTec is becoming more and more popular and, in support of this, we have introduced two new models with 60 litre capacity, a 50% increase over the 40 litre models and available in both traction and non-traction specifications.

Both models of TTB6055 have 60 litre capacity and a 55cm (20") single brush scrubbing path, dual brush pressure selection, built in battery charging, easy fill and easy emptying facilities, with added traction power drive for the 6055T model which would be essential if inclines or ramps are involved.

In terms of operation the Nutronic control system provides for individual speed and water flow rate settings with additional Hi-Lo selection for use in more sensitive areas.

Brush / Pad Selection

Our full range of machines is complemented by an extensive range of brush specifications in order to ensure the highest standards and optimum results in use providing floors you will be proud of.




55cm Light duty scrubbing brush



40/45/55cm Heavy duty scrubbing brush



55cm Long life light duty scrubbing brush



40/55cm Long life heavy duty scrubbing brush



36/40/50cm PadLoc pad drive system

TTB Specifications

Model	Brush Motor	Vac Motor	Power	Run Time	Recharge Time	Pad/Brush width	Capacity	Weight	Drive Speed	Brush Speed	Dimensions WxLxH
TTB1840	400W	300W	2x12V (24V 18Ah)	45min	6hrs	40cm	18L	52Kg	-	150rpm	520x850x1132mm
TTB4045	400W	400W	2x12V (24V 100Ah)	2.25Hrs	8hrs	40/45cm	40L	126Kg	-	100rpm	470x1030x1160mm
TTB4055	400W	400W	2x12V (24V 100Ah)	2.25Hrs	8hrs	50/55cm	40L	128Kg	-	100rpm	560x1060x1160mm
TTB4055T	400W	400W	2x12V (24V 100Ah)	2.25Hrs	8hrs	50/55cm	40L	142Kg	5Kph	100rpm	560x1060x1160mm
TTB6055	400W	400W	2x12V (24V 100Ah)	2.25Hrs	4hrs	50/55cm	60L	158Kg	-	100rpm	550x1280x1160mm
TTB6055T	400W	400W	2x12V (24V 100Ah)	2.25Hrs	4hrs	50/55cm	60L	158Kg	4.2Kph	100rpm	550x1280x1160mm

TwinTec

Professional Battery Models



Flexifill 1m easy filling hose



Plug-in charger system



Nutronic control panel TTB6055T shown



TwinTec Battery

The TwinTec 1840 battery floorcare machine has been engineered to substantially reduce size whilst, at the same time, maximise the performance and handling.

TTB1840

With the total freedom of 24V battery, cable free, operation, this machine will get into areas and places that other machines simply will not go. In many respects, the 1840 allows hard floor maintenance in areas previously cleaned by mopping systems, but some 30% faster and to an improved standard. With its low noise level and unobtrusive appearance this machine will find itself fully at home in many, if not all, commercial environments be it hospitals, clinics, restaurants, cafeterias, offices, banks and hotel lobbies, etc.

Quick change gel battery pack



Easy storage fold down handle



Power and performance where it's needed

With the TwinTec 4045 every part is designed to combine the best in functionality and reliability.

TTB4045

The TTB4045 is the classic Numatic TwinTec 24V battery model. It started its life with 30 litre capacity, now raised to 40 litre, and is today the most popular model worldwide. The premium specification starts with a full stainless steel chassis, Structurofoam tilting brush deck, polyform tanks, fully sealed gel batteries, built in battery charger, heavy duty TwinFlo wet pick up vacuum system and heavy duty geared brush drive.

This classic machine is also fitted with our user friendly Nutronic control system allowing speed and water flow to be individually selected, and with a Hi/Lo setting for more sensitive areas.

Numatic

DeckLoc tilt mechanism




Full stainless steel chassis



Polyform 40 litre clean water tank



TTB4055, TTB4055T



Simple plug-in and charge



TTB4055

TTB4055T

The 4055 is one size up from the 4045 containing all the advanced TwinTec 24V features but with a 20% increased cleaning path.

There are two variations within this model, one with and one without the powered traction drive. The traction drive model must be selected for applications where inclines or wheelchair access ramps are part of the cleaning programme.

Both 4055 models are true workhorses providing exceptional efficiency, easy user friendly operation and stable handling wherever they are used.



Nutronic operational control



2x Fully sealed gel batteries



The Equipment Specialists

+61 8 9249 8744

info@ccequipment.com.au
www.ccequipment.com.au

4 Stanford Way Malaga Western Australia 6090