

# GLAMOUR

## TERRAZZO SEALER



### BENEFITS:

- High gloss
- Hard wearing for high traffic areas
- Scuff mark and abrasion resistant
- Easy application and fast drying

GLAMOUR Terrazzo Sealer provides a tough and durable finish, excellent gloss and outstanding depth. GLAMOUR has excellent levelling characteristics allowing for an even finish with minimal effort.

### DIRECTIONS FOR USE:

**Stripping:** Remove existing polish and/or sealer using Whiteley Industrial Xpoly8 or Zip Strip, ensuring to follow all procedures and directions as per label. Pick up all remaining residue and rinse area with a solution of Tempo HD at a dilution of 9mL/ Litre of water. If required, neutralise the surface (For more information contact Whiteley Industrial). Once the floor is dry it is ready to be sealed.

**Sealing:** Apply first coat of GLAMOUR using a clean applicator, allow 30 minutes drying time between coats (this may vary depending on airflow and drying conditions.) Apply a further 3-4 coats of GLAMOUR ensuring each additional coat is laid on a dry surface. If using Impact as a base for GLAMOUR, apply 1-2 coats of Impact followed by 2-3 coats of GLAMOUR.

**NOTE:** Do not apply when floor temperature is lower than 10°C. Always test on a small inconspicuous area before applying to the whole floor.

**Cutback and Recoat:** Sweep area to be cutback. Mix a solution of Tempo HD at a dilution of 17mL/Litre of water. Apply solution onto surface and allow it to work for 4 to 5 minutes. Depending on condition of floor wet scrub the area using an autoscrubber or swing buffer fitted with blue or black pads. Pick up all solution with autoscrubber, wet vacuum cleaner or mop and bucket. Rinse area with clean water ensuring all residue is gone. When dry, buff area to enhance durability and gloss then sweep to remove all dust. Apply 2-3 coats of GLAMOUR using a clean polish applicator. Always allow each coat to dry before laying the next coat. If time permits, buff the last coat after it is dry to assist with curing and to enhance gloss and durability.

Glamour - July 2014, 1

**Daily Maintenance:** Sweep floor daily, mop and/or scrub floor with Tempo HD at a dilution of 9mL/Litre of water. Use Rejuven8 at a dilution of 17mL/Litre 2-3 times per week, to provide extra wear and durability and to help improve slip resistance. Buff daily.

#### **SAFETY DATA:**

For further information refer to the Material Safety Data Sheet (MSDS) located on the Whiteley Industrial website: [www.whiteley.com.au](http://www.whiteley.com.au)

#### **HEALTH AND SAFETY STATEMENT:**

There is no way of predicting an individual's response to cleaning or disinfecting products. All cleaning and disinfecting products have potential to cause skin and other irritation in susceptible individuals. Direct physical contact with the skin should be avoided. If irritation does occur when using this product or any other cleaning/disinfecting solution then the individual should be removed from direct contact with the solution until a satisfactory safe working environment for that individual is determined.

#### **ENVIRONMENTAL STATEMENT:**

Whiteley Industrial manufactures products that comply with Australian and International environmental policies. Whiteley Industrial aims to ensure that every product is 100% biodegradable, whilst achieving optimal performance and benefit to customers. All Whiteley Industrial products are supplied in 100% recyclable containers.

Whiteley Industrial and its staff are fully committed to ensuring that our Australian environment and those international environs in which our products are used are enhanced by the use of technology, and that these environments are preserved for the enjoyment of future generations.

© 2014 This document remains property of Whiteley Corporation Pty Ltd.

Alterations are not permitted without prior written authorisation from Whiteley Corporation Pty Ltd.

Glamour - July 2014, 2