

Tile & Grout Power

Ultra concentrated tile and grout cleaner



T&G Power is a super-strength tile, grout and hard surface cleaner for blasting through tough soil and carbon build-ups on tile, grout and concrete. It is a skilfully formulated power pack which bursts through the toughest of hard surface grime in industrial deep cleans and restoration.

Description:

T&G Power is a high concentration alkaline cleaner for removing embedded grime, grease, organic soiling and carbons from tiles and hard surfaces.

BENEFITS

- Radical Cleaning Strength – High caustic content provides power cleaning of ceramic tiles and grout, terracotta, concrete and other resilient surfaces.
- Penetration – High tech surfactant system, speciality penetrating agents combined with the powerful alkali blend provides top cleaning performance on a wide spectrum of soil types.
- Grease & Oils – T&G Power cleans with special distinction on oily and greasy soils, carbon build-ups and automotive soiling.
- Low Odour Formula – makes it pleasant and easy to use
- Food Friendly – Ideal for use in food preparation areas, food factories and bakeries.
- Ultra-Concentrate – Highly concentrated – highly economical dilution ratios.

Recommended applications:

Ideally suited for use on all resilient flooring including concrete floors, ceramic tiles, terracotta and grout lines.

Excellent in applications such as industrial kitchens, refuse compactor areas, workshop floors, food processing facilities, bakeries and public eating areas.

Do not use or allow T&G Power to contact painted surfaces, non-ferrous metal surfaces (especially aluminium) and polymer coated flooring. Safe on all man-made tiles, natural stone products, grout and concrete at recommended dilutions.

PRODUCT SPECIFICATIONS

Product code: AP163

pH: 14.0

Dilution: See direction

Fragrance: N/A

Safety: Corrosive

Colour: Clear, light tan liquid

Substrate Suitability: See directions

Packaging: 5Lt, 15Lt, 200Lt & 1000Lt



Tile & Grout Power

Ultra concentrated tile and grout cleaner

HOW TO USE

Read and understand the SDS before use.

Always pre-test in an inconspicuous location for substrate sensitivity to chemicals.

T&G Power is corrosive and appropriate care should be exercised including the use of suitable protective gloves, goggles and protective clothing and warning signage.

Directions:

1. Deep clean applications: Mix 1 part T&G Power with 10 to 20 parts water (100 to 50ml/Litre).
2. Standard cleaning applications: Mix 1 part T&G Power with 80 to 120 parts water (12 to 8ml/Litre).
3. Apply solution with a mop and bucket, auto-scrubber or pressure washer.
4. Agitate heavily soiled areas using a stiff brush, autoscrubber or slow speed rotary scrubber.
5. Allow 10 minutes dwell time and re-agitate
6. Rinse thoroughly with clean water.



The Equipment Specialists

P +618 92498744 E info@ccequipment.com.au
ABN 53 780 286 266 W www.ccequipment.com.au

4 Stanford Way Malaga Western Australia 6090
PO Box 2438 Malaga Western Australia 6944