



# **B 260 R I BP PACK+R120+DOSE+SB**

Excellent vacuuming results, 10 km/h driving speed and designed for tough industrial applications: the ride-on scrubber drier B 260 RI Bp Pack with a battery and an external charger as standard.



EASY Operation selector switch

#### Technical data

Technical data		,
EAN code		4054278954349
Drive type		Battery
Traction drive		Traction motor
Working width of brushes	cm	120
Working width with 1 side brush	mm	1420
Working width, vacuuming	cm	134
Tank of fresh/dirty water		260 / 260
Waste container	1	32
Theoretical area performance	m²/h	max. 12000
Practical area performance	m²	8400
Battery type		Low-maintenance
Battery	V / Ah	36 / 630
Battery runtime	h	max. 5
Battery charging time	h	approx. 12
Driving speed	km/h	max. 10
Brush rotational speed	rpm	1250
Brush contact pressure	kg / g/cm <sup>2</sup>	150 / 168
Aisle turning width	cm	212
Water consumption	l/min	max. 9
Sound pressure level	dB(A)	75
Total permissible weight	kg	1840
Weight without accessories	kg	1448
Dimensions (L × W × H)	mm	2000 × 1380 × 1570

Equipment	
Roller brush	•
Auto Fill	•
Powerful traction drive	•
Battery and charger included	•
Automatic water stop	
DOSE	•
Parking brake	
Integrated sweeper	•
Adjustable steering wheel	
Sweeping function	•
Solenoid valve	
Squeegee, curved	•
Side brush	
2-tank system	•
standard daytime driving light	
Type of suction lips	Linatex*
dosing canister for cleaning agent	
with closed loop system Kärcher colour and operating	
concept	•
Kärcher Intelligent Key System	
(KIK) with over 30 user languages	•
and individual user rights Home Base fastening possibilities	
for mop or similar	•
speed reduction in curves for	-
increased safety	-



electrical and mechanical float switch

Easy Operation selector switch

Included in the scope of supply.

Users must receive training on this device.





### Newly developed roller brush head

- Greatly improved sweeping results and prevents squeegee blockages.
- The rollers can be changed in a matter of seconds and without tools.
- Excellent cleaning results.



### 10 km/h driving speed

- Enables a high area performance in next to no time and quick transportation operations.
- The steering angle sensor acts as a safety feature when driving in curves.
- There is automatic braking if speed is too high when driving in curves.



### Includes two turbines as standard

- Excellent vacuuming results on all surfaces.
- Wear-free Ec turbines.
- Optimised airflow with the newly developed squeegee.



## **BOOK A FREE DEMONSTRATION +618 9249 8744**

### KARCHER

## ACCESSORIES FOR B 260 R I BP PACK+R120+DOSE+SB



		Order no.	Description	
ROLLER BRUSHES				
Roller brush, medium, red, 1118 mm	1	4.250-181.0	Red standard roller brush for maintenance cleaning.	
Roller brush, very hard, Black, 1118 mm	2	5.250-489.0	Very abrasive roller brush for the deep cleaning of hard-wearing floor coverings with very sticky dirt.	
BRUSH HEADS				
Brush head R 120 Industry	3	2.763-058.0	The brush head with 2 roller brushes, 120 cm working width and integrated pre-sweeping function is ideal for cleaning stubborn dirt and its brush can be replaced without any tools.	
WIPING FLAPS				
Linard squeegee blades	4	4.250-167.0	Set of tear-resistant squeegee blades made of Linard. They keep the cleaning water in the working area of the brush head and ensure optimum squeegee performance in turning manoeuvres.	
Squeegee blades, oil-resistant	5	4.250-166.0	Set of low-wear, oil-resistant squeegee blades made from polyurethane. For optimum cleaning results with curve movements and reliable keeping of the cleaning water in the working area of the brush head.	e
SQUEEGEES AND SQUEEGEE BLADES				
Squeegees				
Squeegee, 1340 mm, parabolic	6	4.777-110.0	Parabolic, robust squeegee made from aluminium with 1340 mm suction width and quick coupling. Delivers excellent suction and drying results. Tool-free change of suction lips.	
Squeegee blades				
Suction lips, Linatex <sup>®</sup> , 1490 mm	7	4.250-178.0	Tear-resistant suction lip made from Linatex* with special inlet openings for optimal suction results at crevices and joints. Suitable for parabolic squeegee with 1340 mm suction width.	5
Suction lips, oil-resistant, slotted, 1490 mm	8	4.250-179.0	Low-wear, oil-resistant suction lip made from polyurethane. Three-layer material for high level of flexibility and optimum cleaning properties. For parabolic squeegee with 1340 mm suction width.	
кітѕ				
Side broom / side scrub deck mounting kit				
Side brush B 260 RI R120	9	2.644-372.0	Side brush, right and left. Includes lifting motor and deflector. Removes loose dirt around edges.	
Other attachment kits				_
Side brush spray nozzle attachment kit	10	2.644-392.0	Attachment kit for retrofitting the B 260 R ride-on scrubber dryer with side brushes. The spray nozzles are dust-binding and thereby reduce the amount of dust stirred up when using the side brushes.	
Squeegee impact protection	11	2.644-369.0	Impact protection for our B 260 RI ride-on scrubber drier. Prevents damage to the squeegee when reversing and prevents collisions with tall obstacles, such as palettes.	
HD connection kit	12	2.644-370.0	Attachment kit for the B 260 RI ride-on scrubber dryer to transport the battery-powered HD 4/11 C Bp Pack. Ideal for cleaning hard-to-reach areas. Supplied without high-pressure cleaner.	
Attachment kit stacked bumper roller squeegee	13	4.035-619.0	Additional, non-marking bumper rollers for assembly at the ends of the squeegee. Effectively prevent the squeegee from hooking onto pallets or shelf feet.	
Protective roof	14	2.643-849.0	This high-quality protective roof for the B 250 R scrubber drier (height 2,170 mm including protective roof) protects the operator from falling objects – tested in accordance with EN IEC 60335-2-72.	

Included in the scope of supply.  $\Box$  Available accessories.

## **CONTACT US**



## The Experts in Cleaning Equipment

- +61 9249 8744
- 📵 ccequipment.com.au
- 🖾 info@ccequipment.com.au
- 4 STANFORD WAY, MALAGA WESTERN AUSTRALIA 6090 PO BOX 2438 MALAGA WESTERN AUSTRALIA 6944 ABN: 53 780 286 266