

SCRUBBER DRIERS - WALK BEHIND



CT40

MAX PRODUCTIVITY

 $2250\ m^2/h$

BATTERIES RUNNING TIME

2,5 h

WATER TANK RUNNING TIME

45 min working session



INNOVATIONS





SPECS



INTUITIVE CONTROL PANEL



ANTI-FOAM SYSTEM WITH SPECIAL ELECTROMECHANICAL SUCTION MOTOR PROTECTION



MOST FREQUENTLY USED











CT40 BT50

MUNICIPALITIES

BUILDING SERVICE CONTRACTORS

TECHNICAL DATA

Code

Code	
PERFORMANCE	
Max theoretical productivity	2250 m²/h
Cleaning path	500 mm
Water tank capacity (solution recovery)	40/50 L
Max running time	140 min
Voltage	24(2x12)-105 GEL V-Ah
Installed power	1250 W
Brush pressure	18 kg
Squeegee width	815 mm
Max speed	4,5 km/h
Weight	73 kg
Dimension (LxWxH)	1230 x 516 x 960 mm

CONSUMABLES (Codes available on price list)





SPPV01498 | POLYPROPYLENE (PP) BRUSH

PADS



L-17260 | 20' POLISH PAD - WHITE L-17261 | 20' BUFF PAD - RED L-17262 | 20' SCRUB PAD - BLUE L-1243339 | 20' BUFF PAD - RED (BOX OF 5) L-1243352 | 20' POLISH PAD - WHITE (BOX OF 5)

SQUEEGEE BLADES



MPVR08039 | LATEX FRONT BLADE MPVR08035 | LATEX REAR BLADE

CONTACT US

The Experts in Cleaning Equipment



- +61 9249 8744
- ccequipment.com.au
- info@ccequipment.com.au
- 4 STANFORD WAY, MALAGA WESTERN AUSTRALIA 6090 PO BOX 2438 MALAGA WESTERN AUSTRALIA 6944 ABN: 53 780 286 266